And carrying capacity: 3200kg Actor carrying capacity: 3200kg Actor carrying capacity: 3200kg Semilor to under carring eaccordance to drawing No: PRN A041-Page 1													
1 Flatbar Ust.37–2										6x14x106	0.07		
	DIN 1543(DIN EN 10029)								5				
1	Axle			· .			Ust.37-K		4	ø32x90	0.56		
	DIN 668						DIN 1652		4				
1	Roller						GG-20		- 3	ø150	4.1		
	DIN 1691(DIN EN 1561) PRN A 019(Page 2)												
1	Bolt DIN 933-8.8(DIN EN ISO 4017)						A4H		2	M16x30	0.1		
1	Roller			9			Ust.37-2		$\left  \right $	F1.8x80x235	1.18		
	DIN 10		•••¤						1		1.10		
Qt.							Material		Item	Dimension	Mass.		
	Identity No.				Standard			Description	Kg				
					General		Surface		1	<u> </u>			
					Toleran		finish:						
				-	ISO 27	68-m	ISO 1302			508	00 KVA		
					1395	Date	Name	Tittle:			Scale:		
					Applied			Wheel	n	Ind Accessories (ø150	) ((		
$\left  - \right $					Check Approved				J				
						. 1		Drawing Iden		entification: Sheet No.:			
			+				ايران ترانس			PRN A 0 1 9	2		
Index	Mod.No.	Date	Name	e Approved	REY.		RANSFO REY			Substitued of:	Page No.:		
	G.Z-013(1/										/~/		

.